

承認書

Specification For Approval

COMPANY NAME	
CUSTOMER P/N	
PRODUCT NAME	AC/DC ADAPTER
PARTS P/N	LP0610
DATE	2009-9-21

APPROVED BY	CHECKED BY	PREPARED BY	CUSTOMER APPROVAL SIGNATURE

寶三電子有限公司 POWSUN CO.,LTD.

一厂:

工厂地址: 广东省东莞市清溪镇渔梁围朱屋村

TEL: (0769) 86814578

FAX: (0769) 86814576

二厂:

工厂地址: 广东东莞清溪镇长山头村康怡路 180 号

TEL: (0769) 86814698

FAX: (0769) 86814697

<http://www.powsun.com>

E-mail:powsun@powsun.com

TABLE OF CONTENTS

1. FEATURE -----	2
2. INPUT -----	2
INPUT VOLTAGE-----	2
INPUT FREQUENCY-----	2
INPUT CURRENT-----	2
INRUSH CURRENT-----	2
EFFICIENCY-----	2
INPUT POWER DISSIPATION-----	2
3. OUTPUT -----	2
OUTPUT VOLTAGE-----	2
OUTPUT CURRENT-----	2
REGULATION-----	2
RIPPLE & NOISE-----	2
TOTAL POWER-----	2
4. PROTECTION -----	2
OVER VOLTAGE PROTECTION-----	2
SHORT CIRCUIT PROTECTION-----	2
OVER POWER PROTECTION-----	2
5. SAFETY AND EMI REQUIREMENT -----	3
SAFETY REQUIREMENT-----	3
EMI REQUIREMENT-----	3
LEAKAGE CURRENT-----	3
6. OPERATION & ENVIRONMENT PERFORMANCE -----	3
TEMPERATURE RANGE-----	3
HUMIDITY RANGE(NON CONDENSING)-----	3
7. M.T.B.F -----	3
8. SAMPLE TEST REPORT -----	4、5
9. OUTLINE DRAWING -----	6

POWSUN CO.,LTD SPECIFICATION FOR APPROVAL

1. FEATURE:

- INPUT :UNIVERSAL 100-240 Vac/47-63 Hz INPUT, WITHOUT ANY SLIDE SWITCH
- OUTPUT :+6V /0-1.0A
- DIMENSION :73(D)*27(W)*65(H) mm
- EFFICIENCY :70% TYPICAL
- SAFETY :CB/CE/LVD
- EMI :CISPR 22/FCC/VCCI CLASS B; CONDUCTED & RADIATED MEETED
- HIGH FREQUENCY DESIGN, LESS POWER CONSUMPTION
- OVER VOLTAGE PROTECTION, SHORT CIRCUITED PROTECTION, OVER POWER PROTECTION
- CAN BE USED AT TEL COMMUNICATION, COMPUTER, INDUSTRIAL CONTORLLER & OA SYSTEM

2. INPUT:

2.1 VOLTAGE	UNIVERSAL 100~240Vac,SINGLE PHASE
2.2 FREQUENCY	47HZ~63HZ
2.3 CURRENT	0.5A Max
2.4 INRUSH CURRENT	8A Max/100Vac;16A Max/240Vac (COLD STABT AT 25°C FULL LOAD)
2.5 EFFICIENCY	70% TYPICAL (AT NOMINAL LINE VOLTAGE FULL LOAD)
2.6 INPUT POWER DISSIPATION	UNDER 0.5W < ZERO LOAD 115V/60HZ INPUT UNDER 0.5W < ZERO LOAD 230V/50HZ INPUT

3. OUTPUT:

3.1 DC OUTPUT	VOLTAGE	+6.00V
	CURRENT	1.0A Max
	REGULATION	5.70V Min~6.0V Typ.~6.3V Max
	RIPPLE & NOISE	60mV Max
	TOTAL POWER	6W Max

NOTE: FOR RIPPLE & NOISE MEASUREMENT, USE A 20MHZ BAND WIDTH FREQUENCY OSCILLOSCOPE, AND ADD A 0.1uF MULTILAYER CAP. AND A LOW ESR ELECTROLYTICCAP. (10uF) AT OUTPUT CONNECTOR TERMINALS. (AT NOMINAL LINE VOLTAGE FULL LOAD)

4. PROTECTION:

4.1 OVER VOLTAGE PROTECTION	$V_{out}*(110\% \sim 140\%)$
4.2 SHORT CIRCUIT PROTECTION	AUTOMATIC RECOVERY AFTER SHORT-CIRCUIT FAULT REMOVED
4.3 OVER POWER PROTECTION	THE ADAPTER PROVIDE PROTECTION AT 110%-140% OF RATED OUTPUT POWER

NOTE: WHEN PROTECTION CIRCUIT IS WORKING THE POWER SUPPLY WILL SHUTDOWN, ONCE THE ABNORMAL CONDITIONS ARE REMOVED. THE POWER SUPPLY WILL RESTART AUTOMATICALLY.

POWSUN CO.,LTD SPECIFICATION FOR APPROVAL

5. SAFETY AND EMI REQUIREMENT:

5.1 SAFETY REQUIREMENT

- a. SAFETY : CB/CE/LVD
- b. DIELECTRIC STRENGTH :10mA Max. CUT OFF CURRENT

(1):PRIMARY TO SECONDARY	: 1800Vac FOR 1 MINUTE
(2):PRIMARY TO FRAME GROUND	: 1500Vac FOR 1 MINUTE

c. INSULATION RESISTANCE:

(1):PRIMARY TO SECONDARY	: 10 M OHMS FOR 500Vdc
(2):PRIMARY TO FRAME GROUND	: 10 M OHMS FOR 500Vdc

5.2 EMI REQUIREMENT MEET CISPR 22/FCC/VCC1, CLASS B

5.3 LEAKAGE CURRENT LESS THAN 3.5mA

6.OPERATION & ENVIRONMENT PERFORMANCE:

6.1 TEMPERATURE RANGE

OPERATING	0°C ~ +40°C
STORAGE	-40°C ~+70°C

6.2 HUMIDITY RANGE (NON CONDENSING)

OPERATING	10% ~ 90% RH
STORAGE	5% ~ 95% RH

6.3 COOLING SHOULD OPERATE WITHOUT FAN

7.M.T.B.F.: 50000 HOURS Min ; 40°C SEE CONDITION

TEST REPORT

(I). LINE REGULATION TEST

Test result:

Test condition	Spec.	Reading
90Vac / 50% load	5.70~6.30V	6.09V
115Vac / 50% load	5.70~6.30V	6.09V
132Vac / 50% load	5.70~6.30V	6.09V
180Vac / 50% load	5.70~6.30V	6.09V
230Vac / 50% load	5.70~6.30V	6.09V
264Vac / 50% load	5.70~6.30V	6.09V

(II). EFFICENCY TEST

Test result:

Test condition	Spec.	Reading
115Vac / 100% load	70% Typical	70%
230Vac / 100% load	70% Typical	70%

(III). LOAD REGULATION TEST

Test result:

Test condition	Spec.	Reading
115Vac / 0% load	5.70~6.30V	6.25V
115Vac / 50% load	5.70~6.30V	6.09V
115Vac / 100% load	5.70~6.30V	5.88V
230Vac / 0% load	5.70~6.30V	6.25V
230Vac / 50% load	5.70~6.30V	6.09V
230Vac / 100% load	5.70~6.30V	5.88V

(IV). RIPPLE & NOISE TEST

Test result:

Test condition	Spec.	Reading
115Vac / 100% load	60mV Max	45mV
230Vac / 100% load	60mV Max	30mV

POWSUN CO.,LTD SPECIFICATION FOR APPROVAL

(VI). OVER VOLTAGE PROTECTION

Test result:

Test condition	Spec.	Reading
115Vac / 100% load	Vout*(110%~140%)	115%
230Vac / 100% load	Vout*(110%~140%)	125%

(VII). RISE TIME

Test result:

Test condition	Spec.	Reading
115Vac / 100% load	70mS Max	30mS
230Vac / 100% load	70mS Max	20mS

(VIII). OVER CURRENT PROTECTION

Test result:

Test condition	Spec.	Reading
115Vac / 100% load	Iout*(101%~160%)	120%
230Vac / 100% load	Iout*(101%~140%)	128%

(IX). SHORT CIRCUIT PROTECTION

Test result:

Test condition	Spec.	Reading
115Vac / 100% load	Under 0.8W	OK
230Vac / 100% load	Under 1.0W	OK

POWSUN CO.,LTD SPECIFICATION FOR APPROVAL

