

承認書

Specification For Approval

| | |
|--------------|---------------|
| COMPANY NAME | |
| CUSTOMER P/N | |
| PRODUCT NAME | AC/DC ADAPTER |
| PARTS P/N | CP030030 |
| DATE | 2009-12-15 |

| APPROVED BY | CHECKED BY | PREPARED BY | CUSTOMER APPROVAL SIGNATURE |
|-------------|------------|-------------|-----------------------------|
| | | | |

寶三電子有限公司 POWSUN CO.,LTD.

一厂:

工厂地址: 广东省东莞市清溪镇渔梁围朱屋村

TEL: (0769) 86814578

FAX: (0769) 86814576

二厂:

工厂地址: 广东东莞清溪镇长山头村康怡路 180 号

TEL: (0769) 86814698

FAX: (0769) 86814697

<http://www.powsun.com>

E-mail:powsun@powsun.com

TABLE OF CONTENTS

| | |
|---|-----|
| 1. FEATURE ----- | 2 |
| 2. INPUT ----- | 2 |
| INPUT VOLTAGE----- | 2 |
| INPUT FREQUENCY----- | 2 |
| INPUT CURRENT----- | 2 |
| INRUSH CURRENT----- | 2 |
| EFFICIENCY----- | 2 |
| INPUT POWER DISSIPATION----- | 2 |
| 3. OUTPUT ----- | 2 |
| OUTPUT VOLTAGE----- | 2 |
| OUTPUT CURRENT----- | 2 |
| REGULATION----- | 2 |
| RIPPLE & NOISE----- | 2 |
| TOTAL POWER----- | 2 |
| 4. PROTECTION ----- | 2 |
| OVER VOLTAGE PROTECTION----- | 2 |
| SHORT CIRCUIT PROTECTION----- | 2 |
| OVER POWER PROTECTION----- | 2 |
| 5. SAFETY AND EMI REQUIREMENT ----- | 3 |
| SAFETY REQUIREMENT----- | 3 |
| EMI REQUIREMENT----- | 3 |
| LEAKAGE CURRENT----- | 3 |
| 6. OPERATION & ENVIRONMENT PERFORMANCE ----- | 3 |
| TEMPERATURE RANGE----- | 3 |
| HUMIDITY RANGE(NON CONDENSING)----- | 3 |
| 7. M.T.B.F ----- | 3 |
| 8. SAMPLE TEST REPORT ----- | 4、5 |
| 9. OUTLINE DRAWING ----- | 6 |

POWSUN CO.,LTD SPECIFICATION FOR APPROVAL

1. FEATURE:

- INPUT :UNIVERSAL 100-240 Vac/47-63 Hz INPUT, WITHOUT ANY SLIDE SWITCH
- OUTPUT :+3V / 0-0.3A
- DIMENSION :63(D)*39(W)*67(H) mm
- EFFICIENCY :.75%
- SAFETY :
- EMI :CISPR 22 / FCC /VCCI CLASS B; CONDUCTED & RADIATED MEETED
- HIGH FREQUENCY DESIGN, LESS POWER CONSUMPTION
- OVER VOLTAGE PROTECTION, SHORT CIRCUITED PROTECTION, OVER POWER PROTECTION
- CAN BE USED AT TEL COMMUNICATION, COMPUTER, INDUSTRIAL CONTORLLER & OA SYSTEM

2. INPUT:

| | |
|-----------------------------|--|
| 2.1 VOLTAGE | UNIVERSAL 100~240Vac,SINGLE PHASE |
| 2.2 FREQUENCY | 47HZ~63HZ |
| 2.3 CURRENT | 0.5A Max |
| 2.4 INRUSH CURRENT | 10A Max/100Vac;20A Max/240Vac (COLD STABT AT 25°C FULL LOAD) |
| 2.5 EFFICIENCY | >75% (AT NOMINAL LINE VOLTAGE FULL LOAD) |
| 2.6 INPUT POWER DISSIPATION | UNDER 0.4W < ZERO LOAD 115V/60HZ INPUT |
| | UNDER 0.4W < ZERO LOAD 230V/50HZ INPUT |

3. OUTPUT:

| | | |
|---------------|----------------|-----------------------------|
| 3.1 DC OUTPUT | VOLTAGE | +3V ±5% |
| | CURRENT | 0.3A Max |
| | REGULATION | 2.85V Min~3V Typ.~3.15V Max |
| | RIPPLE & NOISE | 30mV Max |
| | TOTAL POWER | 0.9W Max |

NOTE: FOR RIPPLE & NOISE MEASUREMENT, USE A 20MHZ BAND WIDTH FREQUENCY OSCILLOSCOPE, AND ADD A 0.1uF MULTILAYER CAP. AND A LOW ESR ELECTROLYTICCAP. (10uF) AT OUTPUT CONNECTOR TERMINALS. (AT NOMINAL LINE VOLTAGE FULL LOAD)

4. PROTECTION:

| | |
|------------------------------|---|
| 4.1 OVER VOLTAGE PROTECTION | Vout*(110%~140%) |
| 4.2 SHORT CIRCUIT PROTECTION | AUTOMATIC RECOVERY AFTER SHORT-CIRCUIT FAULT REMOVED |
| 4.3 OVER POWER PROTECTION | THE ADAPTER PROVIDE PROTECTION AT 110%-140% OF RATED OUTPUT POWER |

NOTE: WHEN PROTECTION CIRCUIT IS WORKING THE POWER SUPPLY WILL SHUTDOWN, ONCE THE ABNORMAL CONDITIONS ARE REMOVED. THE POWER SUPPLY WILL RESTART AUTOMATICALLY.

POWSUN CO.,LTD SPECIFICATION FOR APPROVAL

5. SAFETY AND EMI REQUIREMENT:

5.1 SAFETY REQUIREMENT

a. SAFETY :

b. DIELECTRIC STRENGTH :10mA Max. CUT OFF CURRENT

| | |
|-----------------------------|------------------------|
| (1):PRIMARY TO SECONDARY | : 3000Vac FOR 1 MINUTE |
| (2):PRIMARY TO FRAME GROUND | : 1500Vac FOR 1 MINUTE |

c. INSULATION RESISTANCE:

| | |
|-----------------------------|------------------------|
| (1):PRIMARY TO SECONDARY | : 10 M OHMS FOR 500Vdc |
| (2):PRIMARY TO FRAME GROUND | : 10 M OHMS FOR 500Vdc |

5.2 EMI REQUIREMENT MEET CISPR 22/FCC/VCC1, CLASS B

5.3 LEAKAGE CURRENT LESS THAN 3.5mA

6.OPERATION & ENVIRONMENT PERFORMANCE:

6.1 TEMPERATURE RANGE

| | |
|-----------|--------------|
| OPERATING | 0°C ~ +40°C |
| STORAGE | -40°C ~+70°C |

6.2 HUMIDITY RANGE (NON CONDENSING)

| | |
|-----------|--------------|
| OPERATING | 10% ~ 90% RH |
| STORAGE | 5% ~ 95% RH |

6.3 COOLING

SHOULD OPERATE WITHOUT FAN

7.M.T.B.F.:

50000 HOURS Min ; 40°C SEE CONDITION

TEST REPORT

(I). LINE REGULATION TEST

Test result:

| Test condition | Spec. | Reading |
|-------------------|--------------|---------|
| 90Vac / 50% load | 2.85V.~3.15V | 3.05V |
| 115Vac / 50% load | 2.85V.~3.15V | 3.05V |
| 132Vac / 50% load | 2.85V.~3.15V | 3.05V |
| 180Vac / 50% load | 2.85V.~3.15V | 3.05V |
| 230Vac / 50% load | 2.85V.~3.15V | 3.05V |
| 264Vac / 50% load | 2.85V.~3.15V | 3.05V |

(II). EFFICENCY TEST

Test result:

| Test condition | Spec. | Reading |
|--------------------|-------|---------|
| 115Vac / 100% load | >75% | 75% |
| 230Vac / 100% load | >75% | 75% |

(III). LOAD REGULATION TEST

Test result:

| Test condition | Spec. | Reading |
|--------------------|--------------|---------|
| 115Vac / 0% load | 2.85V.~3.15V | 3.11V |
| 115Vac / 50% load | 2.85V.~3.15V | 3.05V |
| 115Vac / 100% load | 2.85V.~3.15V | 2.95V |
| 230Vac / 0% load | 2.85V.~3.15V | 3.11V |
| 230Vac / 50% load | 2.85V.~3.15V | 3.05V |
| 230Vac / 100% load | 2.85V.~3.15V | 2.95V |

(IV).RIPPLE & NOISE TEST

Test result:

| Test condition | Spec. | Reading |
|--------------------|----------|---------|
| 115Vac / 100% load | 30mV Max | 25mV |
| 230Vac / 100% load | 30mV Max | 20mV |

POWSUN CO.,LTD SPECIFICATION FOR APPROVAL

(VI). OVER VOLTAGE PROTECTION

Test result:

| Test condition | Spec. | Reading |
|--------------------|------------------|---------|
| 115Vac / 100% load | Vout*(110%~140%) | 115% |
| 230Vac / 100% load | Vout*(110%~140%) | 125% |

(VII). RISE TIME

Test result:

| Test condition | Spec. | Reading |
|--------------------|----------|---------|
| 115Vac / 100% load | 70mS Max | 40mS |
| 230Vac / 100% load | 70mS Max | 50mS |

(VIII). OVER CURRENT PROTECTION

Test result:

| Test condition | Spec. | Reading |
|--------------------|------------------|---------|
| 115Vac / 100% load | Iout*(101%~160%) | 120% |
| 230Vac / 100% load | Iout*(101%~140%) | 128% |

(IX). SHORT CIRCUIT PROTECTION

Test result:

| Test condition | Spec. | Reading |
|--------------------|------------|---------|
| 115Vac / 100% load | Under 0.5W | OK |
| 230Vac / 100% load | Under 0.6W | OK |

POWSUN CO.,LTD SPECIFICATION FOR APPROVAL

